



S O U T H E R N Hydro-Lawn E A S Y S E E D I N G

PREPARATION

We recommend applying a layer of topsoil to areas that will be hydroseeded. The topsoil should be good quality screened soil applied to a minimum depth of 50mm all over.

- We require the soil to be leveled and not too heavily compacted/rolled.
- Just prior to hydroseed being applied, the soil should be raked up sufficiently to easily push your finger an inch into the soil.
- The soil is to be left dry.
- The sub-base should be firm, and the top soft and fluffy.
- All stones should be removed.
- Any weeds that have come through should be sprayed off.
- We recommend putting in an irrigation system, however any means to apply water to the whole area would suffice. Specific watering requirements should be discussed with Southern Hydrolawn.
- Once the hydroseed has been applied, foot traffic over the area should be kept to a minimum and animals should be kept off the area for at least 3 weeks.
- If there are areas of soils that are of a poorer quality, or that are too hard, you will notice a patchy effect in your lawn, so it is important to have good quality top soil and make sure the soil is raked up.
- Please see our maintenance guidelines document for information on how best to look after your hydroseeded lawn post-application.
- Whilst we do our best to minimise overspray onto walls, fences and into garden areas it is inevitable due to the pressurised spray used in for hydroseeding application. Overspray can be removed whilst hydroseed is wet with a hose and soft brush but needs to be done without damaging the hydroseeded surface. When hydroseed surface has dried it can be walked on to access other areas of overspray to remove with water and a soft brush. The green dye doesn't stain but marks can be left on some paint types. If concerned you can choose to plastic wrap or cover surfaces before we arrive to hydroseed.

Any questions please get in touch.