



S O U T H E R N Hydro-Lawn E A S Y S E E D I N G

PREPARATION



We recommend applying a layer of topsoil to areas that are to have hydrolawn applied. The topsoil should be a good quality screened soil applied to a very minimum of 50mm thick all over.

- ◆ We require the soil to be leveled and not too heavily compacted/rolled.
- ◆ Just prior to hydrolawn being applied, the soil should be raked up sufficiently to easily push your finger an inch into the soil. The soil is to be dry.
- ◆ The sub-base should be firm, and the top soft and fluffy.
- ◆ All stones should be removed.
- ◆ Any weeds that have come through should be sprayed off.
- ◆ We also recommend putting in an irrigation system, however any means to apply water to the whole area would suffice. Specific water requirements should be discussed with Southern Hydrolawn.
- ◆ Once the hydrolawn has been applied, foot traffic over the area should be kept to a minimum and animals should be kept off the area for at least 3 weeks.
- ◆ If there are areas of soils that are of a poorer quality, or that are too hard, you will notice a patchy effect in your lawn, so it is important to have good quality top soil and to make sure the soil is all raked up.

S O U T H E R N
Hydro-Lawn
E A S Y S E E D I N G

Call Johnny on 03 445 1076 - 027 434 3389
Southern Hydro-Lawn
Cromwell

southernhydrolawn@xtra.co.nz
www.southernhydrolawn.co.nz



*Normally ready
to mow in
three weeks*

